

Cladding Mode Free Photosensitive Single-Mode Fiber



Nufern's Cladding Mode Free (CMF) fiber is designed to allow more uniform grating-writing in WDM applications. CMF virtually eliminates all cladding modes allowing tighter channel spacing for high speed communications. Cladding Mode Free fiber is mode-matched to SMF-28TM for telecommunication system use. The polyimide coated CMF fiber is ideally suited for use in a WDM distributed sensing networks operating in high temperature and harsh environments.

Typical Applications

- Couplers
- C+L Band Gratings
- Polyimide Version: Sensors

Features & Benefits

- Excellent cladding mode suppression — allows for tighter channel spacing
- Mode matched to conventional transmission fibers — low splice loss (<0.1 dB typically)
- Polyimide Version: High Temperature coating — enables distributed WDM sensing in harsh environments

Optical Specifications

	CMF	CMF-P
Operating Wavelength	1450 – 1600 nm	1450 – 1600 nm
Core NA	0.130	0.130
Mode Field Diameter	9.1 ± 0.5 μm @ 1550 nm	9.1 ± 0.5 μm @ 1550 nm
Cutoff	1370 ± 70 nm	1370 ± 70 nm

Geometrical & Mechanical Specifications

	CMF	CMF-P
Cladding Diameter	125.0 ± 1.5 μm	125.0 ± 2.0 μm
Core Diameter	8.0 μm	8.0 μm
Coating Diameter	245.0 ± 15.0 μm	145.0 ± 5.0 μm
Coating Concentricity	< 5.0 μm	< 1.5 μm
Core/Clad Offset	≤ 0.50 μm	≤ 0.50 μm
Coating Material	UV Cured, Dual Acrylate	Polyimide
Operating Temperature Range	-55 to 85 °C	-65 to 300 °C
Short Term Bend Radius	≥ 6 mm	≥ 12 mm
Long Term Bend Radius	≥ 13 mm	≥ 25 mm
Proof-test Level	≥ 200 kpsi (1.4 GN/m ²)	≥ 100 kpsi (0.7 GN/m ²)



7 Airport Park Road, East Granby, CT 06026 • 860.408.5000 • Toll-free 866.466.0214 • Fax 860.844.0210 E-mail info @ nufern.com • www.nufern.com • Nufern products are manufactured under an ISO 9001:2008 certified quality management system.



Standard specifications and design parameters are listed above. Specifications are subject to change without notice. Other configurations such as alternative form factors, optimized cut-off and UV cured color coating may be available. Let us know how Nufern can assist with your requirements.